



## Technical specifications

## Measurement & control

Type of media	Gases
Flow range	0...500 ml/min
Accuracy	±0.8% Rd plus ±0.2% FS (N <sub>2</sub> /Air/O <sub>2</sub> )
Repeatability	< ±0.2% Rd
Turndown ratio	1:500
Multi fluid capability	embedded gas data for 22 unique gases plus any mixture of these gases
Pre-installed gases	C2H2 Air C3H4 #1 Ar CO2 CO C3H6 #1 D2 #1 C2H6 C2H4 He H2 Kr CH4 Ne N2 N2O O2 C3F8 C3H6 #2 C3H8 C3H4 #2
Settling time (in control, typical)	<150 ms
Control stability	< ± 0.1% FS (typical for 1 ln/min N2)
Response time (sensor)	<30 ms
Operating temperature	0...+50 °C (32°F - 122°F)
Temperature sensitivity	Flow sensor: zero 0.015% FS/°C; span 0.05% Rd/°C; Pressure sensors: zero 0.16 mbar/°C; span 0.05% Rd/°C
Leak integrity, outboard	tested < 2 x 10 <sup>-9</sup> mbar l/s He
Long term stability	<0.5% FS over period of 3 years, then <0.2% FS per year
Pressure sensitivity	standard: < 0.15% Rd/bar typical N2; with pressure correction: typical factor 5 improved
Pressure range sensor	0...17 bar(a)
Leak-by through closed valve	typical < 1·10 <sup>-4</sup> mbar-l/s He
Mounting	any position, attitude sensitivity negligible
Warm-up time	30 minutes
Storage/transport conditions	0...+50°C, max. 95% RH (non-condensing)

## Approvals

Marking	CE
---------	----

## Mechanical specs

Pressure rating (PN)	16
Ingress protection	IP40
Surface roughness wetted parts	<1.6 µm Ra (<0.8 µm Ra for stainless steel body)
Material wetted parts	aluminium, stainless steel, silicon nitride, epoxy, aluminiumoxide, glas, FKM
Sealing material	FKM 51415
Plunger material	FFKM with PI foil
Process connections	1/8"BSPP female thread (ISO1179-1); compression type, push-in or face seal (VCR/VCO) couplings to be ordered seperately
Max. ΔP	16 bar(d)
Weight	0.2

## Electrical properties

Power supply	+24 Vdc ± 10%
Power consumption	2.5 Watt (typical, in control); add 0.9 Watt for EtherNet communication
Digital communication	Modbus-RTU, Modbus-ASCII, FLOW-BUS, EtherCAT®, EtherNet/IP, Modbus-TCP, POWERLINK, PROFINET

## Electrical interfaces

Service interface	USB-C, Bluetooth
Power (main connector)	9-pin D-sub (male)
Function (main connector)	RS485
Modbus RTU/ASCII/FLOW-BUS	9-pin D-sub (male, main connection)
Modbus TCP / EtherNet/IP / EtherCAT®/ PROFINET / POWERLINK	2x RJ45