



Technical specifications

Measurement & control

| | |
|-------------------------------------|---------------------------------------------------------------------------------------------------------|
| Type of media | Gases |
| Flow range | 0...200 l/n/min |
| Accuracy | ±0.8% Rd plus ±0.2% FS (N ₂ /Air/O ₂) |
| Repeatability | < ±0.2% Rd |
| Turndown ratio | 1:500 |
| Multi fluid capability | embedded gas data for 22 unique gases plus any mixture of these gases |
| Pre-installed gases | C2H2 Ar C3H4 #1 Ar CO2 CO C3H6 #1 D2 #1 C2H6 C2H4 He H2 Kr CH4 Ne N2 N2O O2 C3F8 C3H6 #2 C3H8 C3H4 #2 |
| Settling time (in control, typical) | <1 sec |
| Control stability | < ± 0.1% FS (typical for 1 l/n/min N2) |
| Response time (sensor) | <30 ms |
| Operating temperature | 0...+50 °C (32°F - 122°F) |
| Temperature sensitivity | Flow sensor: zero 0.015% FS/°C; span 0.05% Rd/°C; Pressure sensors: zero 0.16 mbar/°C; span 0.05% Rd/°C |
| Leak integrity, outboard | tested < 2 x 10 ⁻⁹ mbar l/s He |
| Long term stability | <0.5% FS over period of 3 years, then <0.2% FS per year |
| Pressure sensitivity | standard: < 0.15% Rd/bar typical N2; with pressure correction: typical factor 5 improved |
| Pressure range sensor | 0...17 bar(a) |
| Leak-by through closed valve | typical < 0.1% FS Note: a minimum ΔP of 1 bard is required to ensure max. 0.1% FS leak-by rate. |
| Mounting | any position, attitude sensitivity negligible |
| Warm-up time | 30 minutes |
| Storage/transport conditions | 0...+50°C, max. 95% RH (non-condensing) |

Approvals

Mechanical specs

| | |
|--------------------------------|-------------------------------------------------------------------------------|
| Pressure rating (PN) | 16 |
| Ingress protection | IP40 |
| Surface roughness wetted parts | <1.6 µm Ra (<0.8 µm Ra for stainless steel body) |
| Material wetted parts | aluminium, stainless steel, silicon nitride, epoxy, aluminiumoxide, glas, FKM |
| Sealing material | FKM 51415 |
| Plunger material | FFKM with PI foil |
| Process connections | 1/2" BSPF female thread (ISO1179-1); couplings to be ordered seperately |
| Max. ΔP | 16 bar(d) |
| Weight | 626 g; add 50 g for Ethernet interface |

Electrical properties

| | |
|-----------------------|---------------------------------------------------------------------------------------------|
| Power supply | +24 Vdc ± 10% |
| Power consumption | 2.5 Watt (typical, in control); add 0.9 Watt for EtherNet communication |
| Digital communication | Modbus-RTU, Modbus-ASCII, FLOW-BUS, EtherCAT®, EtherNet/IP, Modbus-TCP, POWERLINK, PROFINET |

Electrical interfaces

| | |
|---------------------------------------------------------------|-------------------------------------|
| Service interface | USB-C, Bluetooth |
| Power (main connector) | 9-pin D-sub (male) |
| Function (main connector) | RS485 |
| Modbus RTU/ASCII/FLOW-BUS | 9-pin D-sub (male, main connection) |
| Modbus TCP / EtherNet/IP / EtherCAT®/ PROFINET / POWERLINK | 2x RJ45 |